

CARETREAT ANTIFREEZE

- Biodegradable
- Long term activity
- Direct acting

**Antifreeze on mono ethylene glycol basis,
inhibited for use in cooling water systems**

DESCRIPTION

Antifreeze and anticorrosive liquid for cooling water systems. Caretreat Antifreeze is compatible with all nitrite and phosphate products.

APPLICATIONS / DIRECTIONS FOR USE

Caretreat Antifreeze is dosed pure for frost protection up to and anticorrosive properties. Caretreat Antifreeze can be diluted as well in case lesser frost protection is required.

Dilution Ratio

Weight %	Volume %	Spec. Gravity at 20 °C	Freezing point °C	Boiling point °C
0	0.0	1.000	0	100.0
10	9.1	1.013	-3.5	101.1
20	18.4	1.027	-8	102.2
30	28.0	1.040	-15	103.3
40	37.8	1.057	-24	104.9
50	47.8	1.067	-36	107.2
60	58.0	1.079	-50	109.9
70	68.4	1.090	-49	114.4
80	78.9	1.100	-47	122.2
90	89.4	1.108	-29	137.2
100	100.0	1.115	-13	197.2

PROPERTIES

pH (1 % solution)

7.4

Density

1,057 g/cm³

Flashpoint

Not applicable

Physical state

Liquid

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.

Revision	0	Document number	PDS-08-218
Date of issue	06-11-2019	Page	1 of 1

This information is based on data that we believe to be accurate and reliable and is intended to be used by persons having the knowledge and skill to apply this product properly. We assume no responsibility for results or damages incurred from their use by the Buyer. No liability (including liability for negligence) will attach to Marine Care or its servants or agents arising out of or in connection with or in relation to this product information.



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam Botlek
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. operations@marinecare.nl
W. www.marinecare.nl