

CARETREAT ANTISCALANT WT[®] RO⁺

- Biodegradable
- Low consumption
- Latest polymer technology
- NSF 60/61 approved

High performance Antiscalant for Reversed Osmosis and Ultra filtration systems, running on high carbonate and high sulfate waters

DESCRIPTION

Caretreat Antiscalant WT[®] RO⁺ is a high performance Antiscalant for Reversed Osmosis (RO) and Ultra filtration (UF) systems. The product is based on a blend of the latest technology polymers. Caretreat Antiscalant WT[®] RO⁺ can be used on drinking water, well water, brackish water and seawater. Caretreat Antiscalant WT[®] RO⁺ inhibits Carbonate and Sulfate scales and disperses iron and biological fouling.

ADVANTAGE

- Especially for **high load** RO and UF system
- Outperform all existing products
- Easy to use, neat or diluted
- Low consumption
- High performance on a variety of Carbonate and Sulfate scale
- Can be used on cellulose acetate and polyamide membranes

APPLICATIONS / DIRECTIONS FOR USE

Caretreat Antiscalant WT[®] RO⁺ has to be dosed in the systems feedwater line at a dosing rate of 2 - 5 ppm (mg/l) based on the feedwater flow. The dosing pump should be started/stopped simultaneously with the high pressure RO pump or feedwater pump.



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam Botlek
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. operations@marinecare.nl
W. www.marinecare.nl

Revision	4	Document number	PDS-08-221
Date of issue	21-10-2020	Page	1 of 2

Caretreat Antiscalant WT[®] RO⁺ can be dosed neat or diluted. Dilution should be made with demineralized or RO water. Maximum dilution 1 : 10.

The stock life of the diluted product is 1 - 2 weeks maximum.

To prevent the dilution for microbiological growth add:

- Sodium hydroxide to a pH of 10 - 11 or
- Sodium bisulphite 1 - 2 %.

DOSAGE

Dosingrate Caretreat Antiscalant WT[®] RO⁺ 2 - 5 ppm (mg/l).

Overdosage spills product and can cause polymer fouling.

Underdosage will result in scaling, fouling, reduced systems performance and membrane lifetime.

PROPERTIES

pH	5
Density	1,23 kg/dm ³
Flashpoint	Not applicable
Physical state	liquid

APPROVALS

- Caretreat Antiscalant WT[®] RO⁺ is NSF 60/61 approved for direct food contact

For detailed information on safety and health, please refer to the Material Safety Data Sheet MSDS and/or product label.



MARINE CARE

CARETREAT ANTISCAL-
ANT WT[®] RO⁺

- Biodegradable
- Low consumption
- Latest polymer technology
- NSF 60/61 approved



MARINE CARE BV
Oude Maasweg 35
Port number 4005
3197 KJ Rotterdam Botlek
The Netherlands
T. +31 (0)10 2950342
F. +31 (0)10 2950345
E. soperations@marinecare.nl
W. www.marinecare.nl

Revision	4	Document number	PDS-08-221
Date of issue	21-10-2020	Page	2 of 2

This information is based on data that we believe to be accurate and reliable and is intended to be used by persons having the knowledge and skill to apply this product properly. We assume no responsibility for results or damages incurred from their use by the Buyer. No liability (including liability for negligence) will attach to Marine Care or its servants or agents arising out of or in connection with or in relation to this product information.